

TECHNICAL SPECIFICATIONS

Country of Origin:	New Zealand	Pile Weight:	1360.00g/m ² (40oz)
Colours:	7 Standard	Backing:	Jute
Yarn:	100% Wool	Installation Method:	Conventionally Laid
Surface Texture:	Textured Loop Pile	Type:	Commercial Broadloom
Gauge:	62.9/10cm (1/16th Gauge)	Roll Width:	3.66
Total Product Thickness:	7.5 (+/- 1.0)mm	Pattern Repeat:	Not Applicable
Pile Height:	4.5 (+/- 1.0)mm		

PERFORMANCE

Anti-Static:	(AATCC 134) <3.5KV at 21°C & 20% Relative Humidity
Flammability:	Meets the requirements of NCC Spec. C1.10 relating to fire hazard properties for flooring in Class 2-9 buildings (including health and aged care buildings)~
Light Reflectance:	Available on Request
Stain Resistance:	Natural Wool Fibre Stain Resistance
ACCS Rating:	Residential Extra Heavy Duty & Stairs - 6 Star, Contract Heavy Duty - 3 Star
Contract Guarantee:	7 Year Contract Guarantee Available on Request*
Smoke Value:	84% minutes (Conventionally Laid)
Recommended Adhesive:	Refer to our GH Commercial Adhesive Guide www.ghcommercial.com

SUSTAINABILITY

PVC Minimisation:	PVC Free
Indoor Air Quality:	Green Building Council Compliant for VOC emission rate limits
Product Transparency:	Declare Red List Free
Green Star:	Environmental Certification Scheme (ECS). Level 4 Maximum Points - Certificate #26171
Accreditation:	Manufactured under a quality and environmental system certified and complying with ISO 9001 and ISO 14001 by an accredited certification body.



Declare.



Green Building Council Australia
Member

York Street



14
VINTAGE



42
SAPLING




44
PEPPERWOOD




90
SHADOW



91
ECHO



92
PORTAL



95
MONUMENT

Specifications and colourations are subject to manufacturing tolerances. As part of the GH Commercial continuous improvement program, GH Commercial reserves the right to change the specifications of or delete colours of this product without notice. While all care is taken, product images may vary in colour due to possible printing process variations. Images do not seek to duplicate the exact visual appearance, but serve merely as a guide or point of reference.

All GH Commercial carpets must be installed in accordance with the latest AS2455 and any relevant GH Commercial Carpet Installation Instructions.
Chair pads are recommended under office chairs with roller castors to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear. Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling.
~Test results and certificates are available on request.
*This warranty is in addition to any rights consumers may have under Australian consumer laws. Terms and conditions apply - for full information in respect to the scope of the guarantee please contact your GH Commercial Account Manager or our Head Office.